

**LISTING OF CLAIMS:**

1. (Currently Amended) Process for locating and measuring deformations in soil or infill associated with a civil engineering structure, comprising ~~characterised by the fact that~~

providing at least one geosynthetic fabric (1) having yarns and containing a plurality of optical fibres (2a to 2e) in parallel and capable of transmitting signals, and  
applying the geosynthetic fabric ~~is applied~~ in the said structure or on soil under the said structure,

the said optical fibres containing Bragg gratings (3), evenly spaced in series (4) of N1 consecutive gratings that correspond to the same wavelength, the said series being themselves distributed in identical sets, each of which contains N2 consecutive series that correspond to different wavelengths, and by the fact that, in at least two optical fibres, the numbers N1 of gratings of a series and the numbers N2 of series (4) of a set (5) are determined in such as way that the measurement of differences between the wavelengths of the incident light transmitted in each of the said optical fibres and the wavelengths of the light reflected by the Bragg gratings enable to locate the deformations to which the structure is subjected on the one hand and, on the other, to measure the elongation of the said optical fibres where the deformation occurs.

2. (Original) Process according to claim 1, characterised by the fact that in at least two optical fibres, the numbers N1 of gratings of a series (4) are equal, and the numbers N2 of series (4) of a set (5) are prime to each other.

3. (Original) Process according to claim 1, characterised by the fact that in at least one optical fibre, the number N1 of gratings in a series is equal to the number of gratings of a set in another optical fibre.

4. (Currently Amended) Geosynthetic fabric for locating and measuring deformations in soil or infill associated with a civil engineering structure, comprising ~~characterised by the fact that it contains~~

yarns, and

a plurality of optical fibres (2a to 2e) in parallel, the said optical fibres containing Bragg gratings (3), evenly spaced in series (4) of N1 consecutive gratings that correspond to the same wavelength, the said series (4) being themselves distributed in identical sets (5) of N2 consecutive series that correspond to different wavelengths, and by the fact that, in at least two optical fibres, the numbers N1 of gratings of a series and the numbers N2 of series (4) of a set (5) are determined in such a way that the measurement of differences between the wavelengths of the incident light transmitted in each one of the said optical fibres and the wavelengths of the light reflected by the Bragg gratings enable, on the one hand, to locate the deformations to which the structure is subjected and, on the other hand, to measure the elongation of the said optical fibres where the deformation occurs.

5. (Original) Geosynthetic fabric according to claim 4, characterised by the fact that the optical fibres (2a to 2e) include a sheath to protect them against shear failure, due to aggressive agents in the soil, and against corrosion.

6. (Original) Geosynthetic fabric according to one of the claims 4 or 5, characterised by the fact that the optical fibres (2a to 2e) are laid in the direction of the length of the said geosynthetic fabric.

7. (Previously Presented) Geosynthetic fabric according to any one of the claims 4 or 5, characterised by the fact that the optical fibres are inserted in the said geosynthetic fabric during its manufacture.

8. (Currently Amended) Geosynthetic fabric ~~Process~~ according to claim 4, characterised by the fact that in at least two optical fibres, the numbers N1 of gratings of a series (4) are equal, and the numbers N2 of series (4) of a set (5) are prime to each other.

9. (Currently Amended) Geosynthetic fabric Process according to claim 4, characterised by the fact that in at least one optical fibre, the number N1 of gratings in a series is equal to the number of gratings of a set in another optical fibre.